

GP3 QUALITY FILE

## PRODUCT PASSPORT

Cable holder for direct mounting - 16 cables



PRODUCT REFERENCE

GP3-59247520

DOCUMENT

GP3-59247520

ISSUE DATE

02 AUG 2026

### PRODUCT SPECIFICATION

|                       |                                                                                         |
|-----------------------|-----------------------------------------------------------------------------------------|
| Manufacturer          | GeoPlastic3 (GP3)                                                                       |
| Product type          | Cable holder, double-sided, for direct mounting                                         |
| Material              | HDPE + reinforced engineering polymer blend                                             |
| Colour                | Black                                                                                   |
| Variant / capacity    | 16-cable holder                                                                         |
| Intended application  | Electrical wiring, corrugated pipes, low-current systems and other engineering networks |
| Installation          | Direct mounting; compatible rapid-installation tool system                              |
| Operating temperature | -45 to +60 C                                                                            |
| Warranty              | 36 months                                                                               |
| Storage period        | 12 months from dispatch in the manufacturer's packaging                                 |

### QUALITY CONTROL CHECKLIST

| Inspection area        | Acceptance criteria                                                                                                          | GP3 QC status   |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Appearance             | Must match the approved reference. Minor surface roughness, slight shade variation and minor tooling marks may be permitted. | To be confirmed |
| Product marking        | Molded company mark, product type and production identification must be present.                                             | To be confirmed |
| Halogen screening      | Beilstein qualitative screening: no green glow should be observed.                                                           | To be confirmed |
| Impact resistance      | After impact, no fracture or crack wider than 1 mm and longer than 5 mm at the load point.                                   | To be confirmed |
| Label and traceability | Company mark, type, production date, QC number and packer identification.                                                    | To be confirmed |
| Packaging              | PE bags or cartons inside corrugated transport cartons; do not mix visibly different shades in one package.                  | To be confirmed |
| Colour                 | Colouring must be continuous and uniform.                                                                                    | To be confirmed |

### QUALITY RELEASE STATEMENT

This GeoPlastic3 product passport records the product identity, technical reference data and quality-control criteria for the item described above. Final batch conformity must be confirmed by the authorized GP3 representative before release.

BATCH / LOT NO.

PRODUCTION DATE

QC NO.

AUTHORIZED REPRESENTATIVE

PRODUCT REFERENCE IMAGE



Technical values and QC status must be verified against the relevant GP3 production batch before issue.