



GP3 QUALITY FILE

PRODUCT PASSPORT

D-shaped spacer clip for cable and engineering installation

PRODUCT REFERENCE

GP3-59247600

DOCUMENT

GP3-59247600

ISSUE DATE

02 AUG 2026

PRODUCT SPECIFICATION

Manufacturer	GeoPlastic3 (GP3)
Product type	D-shaped spacer clip
Material	HDPE + reinforced engineering polymer blend
Colour	RAL-9005
Variant / capacity	D-shaped spacer clip for spacer and cable-routing applications
Key dimensions	53 x 40 mm overall envelope; 2.5 mm side-strip thickness; 4 mm overall thickness
Weight	1.40 g
Intended application	Electrical wiring, corrugated pipes, low-current lines and other engineering networks
Installation	Direct mounting; compatible fastening gun/tool system only where approved for the substrate and fastener
Operating temperature	-45 to +60 C
Warranty	36 months
Storage period	12 months from dispatch in the manufacturer's packaging

QUALITY CONTROL CHECKLIST

Inspection area	Acceptance criteria	GP3 QC status
Appearance	Must match the approved reference; minor surface/tooling marks may be permitted.	To be confirmed
Dimensions	Critical dimensions must remain within the applicable GP3 production specification.	To be confirmed
Fastening geometry	Mounting hole, head/profile and cable-routing features must be unobstructed.	To be confirmed
Impact resistance	No fracture or crack that compromises installation or retention at the load point.	To be confirmed
Colour	Colouring must be continuous and uniform for the ordered variant.	To be confirmed
Packaging and traceability	Product reference, production date, QC number and packer identification.	To be confirmed

QUALITY RELEASE STATEMENT

This GeoPlastic3 product passport records the product identity, technical reference data and quality-control criteria for the item described above. Final batch conformity must be confirmed by the authorized GP3 representative before release.

BATCH / LOT NO.

PRODUCTION DATE

QC NO.

AUTHORIZED REPRESENTATIVE

PRODUCT REFERENCE IMAGE

